

**Spinnfaservlies mechanisch verfestigt , 100% Polipropylen erster Qualität , UV-stabilisiert**  
**Geotessile nontessuto , 100% in polipropilene vergine di prima scielta , stabilizzato UV**

01001

Kodex Codice	Länge Lunghezza Rolle - rotolo mt.	Breite larghezza Rolle - rotolo mt.	m2/Rolle m2/rotolo m2	gr./m2 gr./m2	Dicke Spess. mm	Max. Zugkraft tiro max. kN/m	€/m2
2660090	100	2 - 4 - 6	400	<b>90</b>	0,6	7,5 x 6,2	--
2660110	100	2 - 4 - 6	400	<b>110</b>	0,7	8,7 x 8,3	--
2660120	100	2 - 4 - 6	400	<b>120</b>	0,8	9,8 x 8,7	<b>0,77</b>
2660150	100	2 - 4 - 6	400	<b>150</b>	1,0	12,5 x 12	<b>0,87</b>
2660170	100	2 - 4 - 6	400	<b>170</b>	1,1	15,5 x 14,4	--
2660180	100	2 - 4 - 6	400	<b>180</b>	1,2	14,1 x 13,6	--
2660200	100	2 - 4 - 6	400	<b>200</b>	1,2	16,5 x 16,2	<b>1,09</b>
2660220	100	2 - 4 - 6	400	<b>220</b>	1,3	18,0 x 18,0	--
2660250	100	2 - 4 - 6	400	<b>250</b>	1,4	21,0 x 20,5	<b>1,34</b>
2660280	100	2 - 4 - 6	400	<b>280</b>	1,6	23,0 x 22,2	--
2660300	100	2 - 4 - 6	400	<b>300</b>	1,6	25,3 x 24,5	<b>1,59</b>
2660350	100	2 - 4 - 6	400	<b>350</b>	1,7	30,0 x 29,7	<b>1,84</b>
2660370	100	2 - 4 - 6	400	<b>370</b>	1,8	31,8 x 31,3	--
2660400	80	2 - 4 - 6	320	<b>400</b>	2,0	34,0 x 33,0	<b>2,09</b>
2660500	80	2 - 4 - 6	320	<b>500</b>	2,5	38,0 x 36,5	<b>2,58</b>
2660600	80	2 - 4 - 6	320	<b>600</b>			--
2660800	80	2 - 4 - 6	320	<b>800</b>			--
2661000	50	2 - 4 - 6	200	<b>1000</b>			--
2661200	50	2 - 4 - 6	200	<b>1200</b>			--
2661500	50	2 - 4 - 6	200	<b>1500</b>			--
2662000	50	2 - 4 - 6	200	<b>2000</b>			--

