

Druckregler "EURO" Mod. 300000 mit Holländer A-Gewinde, aus Messing, max. Betriebsdruck 25 Bar, Reduktionsfeld 0,5 - 6 Bar.

Riduttore di pressione "EURO" mod. 300000 con bocchettoni filettati maschio, in ottone, pressione max. 25 bar, campo di taratura 0,5 - 6 bar.

07501

PN 25



Kodex - Codice	Ø	Länge - Lunghezza	€/St. - €/pz.
		mm	
R30004	1/2"	140	141,69
R30005	3/4"	160	164,22
R30006	1"	181	199,29
R30007	1 1/4"	190	273,69
R30008	1 1/2"	218	486,08
R30009	2"	240	554,89

Druckregler "EURO" Mod. 300050 mit Holländer A-Gewinde, aus Messing, max. Betriebsdruck 25 Bar, Reduktionsfeld 0,5 - 6 Bar mit integriertem Feinfilter.

Riduttore di pressione "EURO" mod. 300050 con bocchettoni filettati maschio, in ottone, pressione max. 25 bar, campo di taratura 0,5 - 6 bar con filtro autopulente integrato.

07502

PN 25



Kodex - Codice	Ø	Länge - Lunghezza	€/St. - €/pz.
		mm	
R30054	1/2"	140	207,62
R30055	3/4"	160	242,30
R30056	1"	181	292,96
R30057	1 1/4"	190	403,62