

Spinnfaservlies mechanisch verfestigt , 100% Polipropylen erster Qualität , UV-stabilisiert
 Geotessile nontessuto , 100% in polipropilene vergine di prima scielta , stabilizzato UV

Kodex Codice	Länge Llunghezza	Breite larghezza	m2/Rolle m2/rotolo	gr./m2 gr./m2	Dicke Spess.	Max. Zugkraft tiro max.	€/m2
	Rolle - rotolo mt.	Rolle - rotolo mt.	m2		mm	kN/m	
2660090	100	2 - 4 - 6	400	90	0,6	7,5 x 6,2	<i>auf Anfrage</i>
2660110	100	2 - 4 - 6	400	110	0,7	8,7 x 8,3	<i>a richiesta</i>
2660120	100	2 - 4 - 6	400	120	0,8	9,8 x 8,7	<i>auf Anfrage</i>
2660150	100	2 - 4 - 6	400	150	1,0	12,5 x 12	<i>a richiesta</i>
2660170	100	2 - 4 - 6	400	170	1,1	15,5 x 14,4	<i>auf Anfrage</i>
2660180	100	2 - 4 - 6	400	180	1,2	14,1 x 13,6	<i>a richiesta</i>
PPST200	100	2 - 4 - 6	400	200	1,3	16,0 x 16,0	1,50 €
2660220	100	2 - 4 - 6	400	220	1,3	18,0 x 18,0	<i>auf Anfrage</i>
2660250	100	2 - 4 - 6	400	250	1,4	21,0 x 20,5	<i>a richiesta</i>
2660280	100	2 - 4 - 6	400	280	1,6	23,0 x 22,2	<i>auf Anfrage</i>
PPST300	100	2 - 4 - 6	400	300	1,6	25,0 x 25,0	2,23 €
2660350	100	2 - 4 - 6	400	350	1,7	30,0 x 29,7	<i>auf Anfrage</i>
2660370	100	2 - 4 - 6	400	370	1,8	31,8 x 31,3	<i>a richiesta</i>
2660400	80	2 - 4 - 6	320	400	2,0	34,0 x 33,0	<i>auf Anfrage</i>
2660500	80	2 - 4 - 6	320	500	2,5	38,0 x 36,5	<i>a richiesta</i>
2660600	80	2 - 4 - 6	320	600			<i>auf Anfrage</i>
2660800	80	2 - 4 - 6	320	800			<i>a richiesta</i>
2661000	50	2 - 4 - 6	200	1000			<i>auf Anfrage</i>
2661200	50	2 - 4 - 6	200	1200			<i>a richiesta</i>
2661500	50	2 - 4 - 6	200	1500			<i>auf Anfrage</i>
2662000	50	2 - 4 - 6	200	2000			<i>a richiesta</i>

